

Thermohospital

Disinfectant-resistant emulsion polish

- Self-shining polymer emulsion for use in hospitals and retirement homes
- ▲ Outstanding film-forming properties
- A Particularly hard-wearing, dirt-repelling, wipe-proof and slip resistant
- Very good water resistance
- A Resistant to surface disinfectant products
- Temporary partial solution of the maintenance film by hand disinfectants possible





Area of application

Can be used on water-resistant, coatable, stripped floorings, e.g. PVC, rubber, linoleum, absorbent natural and artificial stone. Please perform an adhesion test before using on floorings with a PU or PE wear layer.

Application

Please test on a small inconspicuous spot before first application. Do not let the product dry on the mop. Close canister immediately after use. Avoid draughts during use and drying.

Coating:

Depending on the absorbency of the surface, 2–3 layers at intervals of approx. 30 minutes. Following stripping and a short drying time, apply a thin coat of undiluted product, e.g. using a flat mop or waxer. Consumption: 25.0 ml/m² per application.



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only! Protect from frost.

Ingredients

Synthetic dispersions, hard polyethylene waxes, water-soluble solvents, softeners, preservatives. pH value (concentrate): approx. 8.5

Art. No. j200605

Packaging unit (PU)
Carton of 2 x 5 L PCR-canisters

Numbers of PU per pallet

56

30.10.2021 Page 1 of 1