

Kiehl-Eco-Refresher

Water-based film-forming wood maintenance oil

- Depending on the type of floor, emphasises the colouring
- Matt drying
- Fragrance free
- Free from heavy metals, solvents, formaldehyde and fragrances
- Oxidation hardening and vapour diffusion
- Optimum polished finish
- Easy to use





Area of application

For initial and re-oiling of real wood surfaces, e.g. parquet and planks. Do not use on sealed, coated or waxed surfaces.

Application

Please test on a small inconspicuous spot before first application. The surfaces must be clean, release-agent free and properly prepared to ensure faultless adhesion and appearance. Shake well before use. The floor and product temperature must be between 15 °C and 25 °C. Avoid draughts during use and drying. Ventilate rooms properly after drying.

Preparation of the surface:

Dry clean parquet surfaces before coating (use Kiehl-Legno pad). Accruing dust must be removed.

Initial oiling (film forming):

Detailed instructions are available on request. Consumption: 50.0 ml/m².

Re-oiling (film forming):

Depending on the absorbency of the surface, 1–2 layers at intervals of approx. 120 minutes.

After preparing the surfaces, apply a thin coat of undiluted product, e.g. using a flat mop or waxer. Safe to walk on after approx. 2 hours and wipe-proof after approx. 2 days. Consumption: 20.0 ml/m².

Polishing:

The oil layer can be compacted and polished until it shines up to 24 h after drying by polishing (approx. 400 – 1000 rpm) and Multi-Disc.

Clean tools with water.



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only! Protect from frost. Proper dosage saves costs and minimises environmental impacts. Surfactants based on vegetable raw materials. Packaging material is recyclable.

Ingredients

Nonionic surfactants < 5%, waxes, drying agents, vegetal oil components, preservatives. pH value (concentrate): approx. 8.5

Art. No. j221605

