



Carpasol

Carpet cleaner for spray extraction machines

- ▲ Cleans carpets deep into the fibres
- Quickly dissolves the dirt
- Forms vacuumable agglomerates comprising polymers and dirt particles
- ▲ Agglomerates do not adhere with the carpet fibres (anti-soil effect)
- ▲ Can also be used with the textile pad method



Area of application

Can be used on colourfast and moisture-resistant textile floor coverings and covers.

Application

Please test on a small inconspicuous spot before first application. Clean the carpet thoroughly first.

Spray extraction:

Depending on the degree of soiling, 0.5–1 L to 8 L of cold water.

Pour cleaning solution into the freshwater tank. Pre-spray stains with the floor nozzle. Move the floor nozzle over the carpet in parallel, overlapping paths. Fluff up carpet pile and do not walk on until fully dry. Consumption: 100.0 ml/m².

Textile pad method:

Depending on the degree of soiling, 100–150 ml to 1 L of cold water.

Pour cleaning solution into the spray can. Spray textile pad with cleaning solution and place under rotary floor machine. Spray sparingly onto approx. 1m² of carpet and work in circular motions. Turn over or replace soiled textile pad. Consumption: 5.0 ml/m².





Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients (according to 648/2004/EC)

Nonionic surfactants < 5%, anionic surfactants < 5%, phosphates 5–15%, maintenance substances, water-soluble solvents, fragrances. pH value (concentrate): approx. 9.5 pH value (ready-to-use solution): approx. 8.5

 Art. No.
 Packaging unit (PU)
 Numbers of PU per pallet

 j600510
 10 L canister
 60

 j600572
 200 L drum
 2

30.10.2021 Page 1 of 1