

Kiehl-Wax-Ex

Wax remover

- ▲ Only contains de-aromatised, low-odour solvents
- ▲ Prevents the swelling of water-sensitive floorings
- ▲ Product is not water-miscible
- ▲ Do not allow product to get into wastewater



Area of application

For the removal of solvent-based wax, tar, oil, bitumen and scuff and heel marks. Only use on solvent-resistant base materials, such as wood, cork and clay tiles (cotto).

Application

The floor and product temperature must be between 15 °C and 25 °C. Ventilate rooms well during and after cleaning.

Wax removal:

Distribute the undiluted product on approx. 5 m² of the floor area. Clean the area by hand or using a rotary floor machine. Use a cleaning rag or other absorbent material to soak up the dissolved dirt. Do not use a wet vacuum cleaner. Then treat the next 5 m² of the floor in the same way. Consumption: 150.0–200.0 ml/m².

Spray cleaning (removing scuff and heel marks):

Use a rotary floor machine to work the undiluted product.



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only! Do not smoke!

Ingredients

Water-insoluble solvents.

Classification

Classification (in concentrate): GHS08, Danger. H304 May be fatal if swallowed and enters airways. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 Do NOT induce vomiting. EUH066 Repeated exposure may cause skin dryness or cracking. Contains: C-10-12 Alkane/Cycloalkane (INCI)

Art. No.

j220270

Packaging unit (PU)

Carton of 2 x 5 L tin canisters

Numbers of PU per pallet

60