

Thermodur-diamant

High solid acrylic emulsion polish

- ▲ Three-dimensionally cross-linked polymer emulsion for use in very highly frequented areas
- ▲ Outstanding film-forming properties
- ▲ Very high filling capacity
- ▲ High solids content
- ▲ Very good water resistance
- ▲ Extremely abrasion and scratch-proof
- ▲ Resistant to surface disinfectant products



Area of application

Can be used on water-resistant, coatable, stripped floorings, e.g. PVC, rubber, linoleum, absorbent natural and artificial stone. Please perform an adhesion test before using on floorings with a PU or PE wear layer.

Application

Please test on a small inconspicuous spot before first application. Do not let the product dry on the mop. Close canister immediately after use. Avoid draughts during use and drying.

Coating:

Depending on the absorbency of the surface, 1–2 layers at intervals of approx. 60 minutes. Following stripping and a short drying time, apply a thin coat of undiluted product, e.g. using a flat mop or waxer. Consumption: 30.0 ml/m² per application.

To prevent changes to the maintenance film surface, cleaning products with a high solvent content may only be used for stripping. Due to a significantly increased hardening time if more than two layers are applied, in this case the coating may only be cleaned using dry methods during the first 48 hours.



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only! Protect from frost.

Ingredients

Synthetic dispersions, hard polyethylene waxes, water-soluble solvents, resins, softeners, preservatives.
pH value (concentrate): approx. 8.5

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j201105	Carton of 2 x 5 L PCR canisters	56